



# ADDERLink X-DVI

The AdderLink X-DVI is the first extender to transmit both full DVI video as well as USB keyboard and mouse over a single CAT 6 cable

The AdderLink X-DVI allows users to distribute control of any computer which uses DVI video and USB for keyboard and mouse interface. The X-DVI can deliver perfect digital video at distances up to 50 meters and resolutions up to 165 MPixels per second (e.g. 1920x1200 @ 60Hz or 3840 x 2400 @ 17Hz). In operation, the X-DVI is truly plug and play, delivering full EDID data from computer to screen ensuring your hardware is always setup to deliver optimal display performance.



## FEATURES

### Full single link DVI extender

The AdderLink X-DVI extender is designed to deliver full single link DVI digital video resolutions up to 165 MPixels per second. 165MPixels per second is the maximum data rate available on single link DVI connections, and is achieved without the need to compress data in any way. Resolutions supported by single link DVI range from 640 x 480 @ 60 Hz (25 MPixels/s) through to 3840 x 2400 @ 17Hz (164 MPixels/s).

### USB keyboard and mouse extender

Alongside fully un-compressed DVI video, the AdderLink X-DVI also delivers bidirectional USB HID data allowing you to extend keyboards and mice over 50 meters on the same CATx cable. This makes the X-DVI perfect for distributed workstations where you want to reduce environmental concerns such as heat and noise. A typical example of this would be post production suites. By centralising your workstations, you can also extend operational life-span by ensuring optimal temperature control, and minimal physical disturbance.

### Single CATx distribution

AdderLink X-DVI requires just one CATx (CAT6 recommended) cable. Other solutions available require two cables to carry DVI and DDC EDID. The X-DVI delivers this alongside USB data over a single CATx cable. Dependent upon cable type and quality, distances in excess of those quoted by Adder may also be achieved.

### DVI-D digital Video

The AdderLink X-DVI is specifically designed to carry Digital video over 50 meters. By maintaining the video in

a purely digital domain, no loss of quality through D/A or A/D conversion will be experienced, ensuring the display output (LCD panel for example) is exactly the same as the signal produced by the display adapter (video card).

### Extended profile DDC EDID


The AdderLink X-DVI carries extended profile DDC EDID data from your display device to the display adapter to ensure that your system is configured to deliver optimal video performance. The extended profile DDC EDID is particularly important when extending video to high performance display devices. This is essential for professional graphics users such as post production, broadcast, architecture, graphic design, medical imaging, CAD or any other applications where display performance is critical.

### Intelligent cable modelling

The X-DVI has been designed to be used in many different environments across many different types and makes of cable. To ensure the quality of your DVI signal is always optimal, Adder have modeled a broad range of cables and integrated these models into the X-DVI. As a result, the user has greater flexibility over the CATx connection, allowing you to make use of existing CATx infrastructure.

### Interface/mains power options

The AdderLink X-DVI transmitter can be powered directly via the USB link, reducing cable clutter. If you prefer, a mains power adapter is also available.





# ADDERLink X-DVI

The AdderLink X-DVI is the first extender to transmit both full DVI video as well as USB keyboard and mouse over a single CAT 6 cable

## TECHNICAL SPECIFICATIONS

<b>Video Resolution</b>	Single link DVI video resolution up to a maximum pixel rate of 165MP/s
<b>Extension Distance:</b>	Maximum of 50m using CATx S/FTP cable
<b>O/S Compatability:</b>	Operating system independent
<b>Connectors (local / remote):</b>	Local end: DVI-D, USB B, optional power jack, RJ45 Remote end: DVI-D, dual USB A, power jack,
<b>Physical:</b>	Local: All metal case, 120mm / 4.7" (w) x 75mm / 3"(d) x 26mm / 1" (h) 319g / 0.7 lb. Remote: All metal case, 120mm / 4.7" (w) x 75mm / 3"(d) x 26mm / 1" (h) 323g / 0.7 lb.
<b>Power :</b>	Local interface powered, optional +5V DC; remote end +5V
<b>Operating temperature:</b>	0-40 °C
<b>Approvals</b>	CE, FCC
<b>Order Codes</b>	X-DVI-XX
XX= Mains Lead Country Code: UK = United Kingdom US = United States EURO = Europe AUS = Australia	

### Example Single Link DVI Resolutions

In reality there are many more resolutions available over Single Link DVI, all of which are supported by the X-DVI. Below are a few example profiles:

Scheme	Resolution	Frequency	Data Format	Data Rate
HDTV	1920 x 1080	60 Hz	CVT-R	139 MP/s
UXGA	1600 x 1200	60 Hz	GTF	161 MP/s
WUXGA	1920 x 1200	60 Hz	CVT-R	154 MP/s
SXGA	1280 x 1024	85 Hz	GTF	159 MP/s
WXGA+	1440 x 900	60 Hz		107 MP/s
WQUXGA	3840 x 2400	17 Hz		164 MP/s

Local, Remote and Global Computer Control



#### ADDER TECHNOLOGY

Technology House, Trafalgar Way, Bar Hill,  
Cambridge, CB23 8SQ UK  
Tel: +44 (0)1954 780044 Fax: +44 (0)1954 780081  
email: sales@adder.com www.adder.com

#### ADDER CORPORATION

29 Water Street  
Newburyport, MA 01950 USA  
Tel: +1 888 932 3337 Fax: +1 888 275 1117  
email: usasales@adder.com www.adder.com

#### ADDER TECHNOLOGY ASIA PACIFIC

6 New Industrial Road  
#07-01 Hoe Huat Industrial Building, Singapore 536199  
Tel: +65 6288 5767 Fax: +65 6284 1150  
email: asiasales@adder.com www.adder.com